

Lektriever® 120

Automated vertical filing system
for suspended files



Technical data

Unit dimensions

Overall width	2560 mm 2947 mm
Overall depth excluding posting board	1155 mm
Depth of posting board	300 mm
Height from floor to posting board	750 mm

Electrics

Standard 220/250 V 110/127 V
50/60 Hz A.C. supply.
Alternative voltages available.

Colour

Posting board, Access panel,
upper front panel and rear panels:
Light Grey
Remainder:
Signal Grey

Benefits at a glance:

- Increase speed and efficiency
- Improve productivity
- Increase storage capacity
- Eliminate misfiling
- Improve records security
- Enhance office environment

The Kardex Lektriever is capable of accepting all makes of suspended filing so if you already use this type of filing system the benefits of automation can be enjoyed without difficulty.

Supplied complete with fixed posting board, carrier selection panel, electronic safety photocells and mechanical safety devices, by-pass switch and lockable sliding door as standard. All units for suspended filing in pull-out hanging frames are equipped with accident protection diagonal photocells. A front light-box over the working area is available as an optional extra.

Lektrievers are provided with a front access panel protected by a micro-switch for the retrieval of items accidentally dropped into the conveyor compartment. Kardex Lektrievers can be installed side by side or back to back,

as all routine maintenance can be performed from the front of the machine. Should power fail, the unit can be operated by a handle, so that contents can still be obtained. When power is restored a safety cut-out stops automatic movement until the handle is removed.



Lektriever 120 for suspended filing systems: Saving space, boosting productivity



Cat. No.	No. of Carriers	Average Access Time Seconds	Machine Height mm	Minimum Room Height mm	Weight Unloaded kg		Filing Capacity cm	
					Unit Width 2560 mm	Unit Width 2947 mm	Unit Width 2560 mm	Unit Width 2947 mm
For foolscap suspended folders with hanging bars 390 mm centre to centre. Maximum folder height including tab 282 mm								
1112	11	4.7	2250	2270	1238	1384	2145	2574
1212	12	5.1	2400	2420	1315	1472	2340	2808
1312	13	5.5	2550	2570	1394	1561	2535	3042
1412	14	5.9	2700	2720	1472	1649	2730	3276
1512	15	6.4	2850	2870	1550	1738	2925	3510
1612	16	6.8	3050	3070	1634	1833	3120	3744
1712	17	7.2	3200	3220	1713	1921	3315	3978
1812	18	7.6	3350	3370	1791	2009	3510	4212
1912	19	8.1	3500	3520	1869	2098	3705	4446
2012	20	8.5	3650	3670	1948	2187	3900	4680



Made in Germany

Further information:
www.kardex-remstar.com

Kardex Systems Ltd

P.O. Box 53133
3300 Limassol
Cyprus

Tel +357 25 875600
Fax +357 25 590091
info.remstar.cy@kardex.com