



Fig. Safe AM25, hinge right  
K-Lock Cawi 2 keys (95 mm), 2 inside lockers, 1 shelf

EN1143-1  
Burglary protection

VdS  
Grade I

ECB-S  
Grade I

ISO  
Class EN 1

R2B  
Class I E

DIN  
4102 (light fire protection)

Domestic insurable  
up to EUR 65.000

Commercial insurable  
up to EUR 20.000

### [ Safes ]

### [ Type AM ]

AM series safes offer lots of space and the option of additional locks to give dual control. All models are pre-fitted to enable connection to a burglar alarm system. Even the smallest model (AM10) has enough space to accommodate up to 6 file folders.

### [ Product information ]

Hinge	DIN right – model designation R option: DIN left
Door opening angle	180°
Body	double-walled, filled with high resistant barrier material
Door structure	triple-walled, filled with high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for floor and rear wall anchoring anchoring bolts and shields are supplied option: additional anchoring holes (customer specifies position)
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock	model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm) model designation E – electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)
Equipment	shelf adjustable (height setting 85 mm) option: additional shelf, inside locker, drawer, pull-out shelf, key rack
Accessories	option: certified steel plinth to raise the level of the safe, fire protection door rebate seals, alarm switch set, interior lighting

Model	Outside dimensions h x w x d (mm)	Inside dimensions h x w x d (mm)	SH	Volume (l)	Weight (appr. kg)
AM10RK / AM10RE	395 x 545 x 442	345 x 495 x 310	1	53	125
AM15RK / AM15RE	565 x 545 x 442	515 x 495 x 310	1	79	155
AM20RK / AM20RE	735 x 545 x 442	685 x 495 x 310	1	105	185
AM25RK / AM25RE	905 x 545 x 442	855 x 495 x 310	2	131	215
AM30RK / AM30RE	1075 x 545 x 442	1025 x 495 x 310	2	157	245
AM35RK / AM35RE	1245 x 545 x 442	1195 x 495 x 310	3	183	280
AM40RK / AM40RE	1415 x 545 x 442	1365 x 495 x 310	3	209	310

SH = Shelf

### [ Equipment options ]

