



EN1143-1
Burglary protection

EN15659
Fire protection

VdS
Grade I

Grade I + LFS30P
(AP10 - LFS60P)

Class EN 1

Class I E

Domestic insurable
up to EUR 65.000

Commercial insurable
up to EUR 20.000

Fig. Safe AP10, hinge right
K-Lock Cawi 2 keys (145 mm), without equipment

[Safes]

[Type AP]

In addition to the qualities of the AM safes, the AP series safes offer certified protection against fire. Additional heat absorbent materials and fire and smoke protection seals in the door rebates provide fire protection – tested and certified in grade LFS30P (AP10 - LFS60P).

[Product information]

Hinge	DIN right – model designation R option: DIN left
Door opening angle	180°
Body	double-walled, filled with high resistant barrier and heat absorbent materials
Door structure	triple-walled with double rebate, filled with high resistant barrier material and heat absorbent materials, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance, door rebate fitted with several fire and smoke protection seals
Locking mechanism	three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for floor and rear wall anchoring anchoring bolts and shields are supplied
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock	model designation K – double-bit lock VdS class 1, Cawi 2 keys (145 mm) model designation E – electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)
Equipment	shelf adjustable (height setting 85 mm) option: additional shelf, inside locker, drawer, pull-out shelf, key rack
Accessories	option: alarm switch set, interior lighting

Model	Outside dimensions h x w x d (mm)	Inside dimensions h x w x d (mm)	SH	Volume (l)	Weight (appr. kg)
AP10RK / AP10RE *	474 x 605 x 522	360 x 495 x 310	1	55	180
AP15RK / AP15RE	629 x 605 x 522	515 x 495 x 310	1	79	220
AP20RK / AP20RE	799 x 605 x 522	685 x 495 x 310	1	105	260
AP25RK / AP25RE	969 x 605 x 522	855 x 495 x 310	2	131	305
AP30RK / AP30RE	1139 x 605 x 522	1025 x 495 x 310	2	157	350
AP35RK / AP35RE	1309 x 605 x 522	1195 x 495 x 310	3	183	390
AP40RK / AP40RE	1479 x 605 x 522	1365 x 495 x 310	3	209	435

SH = Shelf

* AP10 fire protection LFS60P

[Equipment options]

