



Fig. Safe BP15, hinge right  
E-Lock M-Locks 3520, 1 shelf

EN1143-1  
Burglary protection

EN15659  
Fire protection

VdS  
Grade II

Grade II + LFS30P  
(BP10/BP41 - LFS60P)

Class EN 2

Class II E

Domestic insurable  
up to EUR 100.000

Commercial insurable  
up to EUR 50.000

### [ Safes ]

### [ Type BP ]

In addition to the qualities of the BM safes, the BP series safes offer certified protection against fire. Additional heat absorbent materials and fire and smoke protection seals in the door rebates provide fire protection – tested and certified in grade LFS30P (BP10/BP41 - LFS60P).

### [ Product information ]

Hinge	DIN right – model designation R option: DIN left
Door opening angle	180°
Body	double-walled, filled with armoured, high resistant barrier and heat absorbent materials
Door structure	triple-walled with double rebate, filled with armoured, high resistant barrier material and heat absorbent materials, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance, door rebate fitted with several fire and smoke protection seals
Locking mechanism	three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Anchoring	prepared for floor and rear wall anchoring anchoring bolts and shields are supplied
Alarm connection	VdS-certified cable channels to allow connection to a burglar alarm system
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock	model designation K – double-bit lock VdS class 1, Cawi 2 keys (145 mm) model designation E – electronic lock VdS class 2, M-Locks EM3520 option: other lock models (primary lock or possible secondary locks)
Equipment	shelf adjustable (height setting 85 mm) option: additional shelf, inside locker, drawer, pull-out shelf, key rack
Accessories	option: alarm switch set, interior lighting

Model	Outside dimensions h x w x d (mm)	Inside dimensions h x w x d (mm)	SH	Volume (l)	Weight (appr. kg)
BP10RK / BP10RE *	474 x 605 x 522	360 x 495 x 310	1	55	190
BP15RK / BP15RE	629 x 605 x 522	515 x 495 x 310	1	79	235
BP20RK / BP20RE	799 x 605 x 522	685 x 495 x 310	1	105	280
BP25RK / BP25RE	969 x 605 x 522	855 x 495 x 310	2	131	325
BP30RK / BP30RE	1139 x 605 x 522	1025 x 495 x 310	2	157	375
BP35RK / BP35RE	1309 x 605 x 522	1195 x 495 x 310	3	183	420
BP40RK / BP40RE	1479 x 605 x 522	1365 x 495 x 310	3	209	465
BP41RK / BP41RE *	1479 x 765 x 582	1365 x 655 x 370	3	331	580

SH = Shelf

\* BP10/BP41 fire protection LFS60P

### [ Equipment options ]

