









-  EN1143-1  
Burglary protection
-  EN15659  
Fire protection (option)
-  VdS  
Grade IV
-  ECB-S  
Grade IV  
+ LFS60P (option)
-  ISO  
Class EN 4
-  DIN  
4102 (light fire protection)



-  Domestic insurable  
up to EUR 400.000
-  Commercial insurable  
up to EUR 150.000

Fig. Safe DWS0850, hinge right  
E-Lock Kaba Paxos advance Set 1 (keypad) + Set 5, 1 shelf

Model	Outside dimensions			Inside dimensions			SH	Volume (l)	Weight (appr. kg)
	h	x	w x d (mm)	h	x	w x d (mm)			
DWS0849R	848	x	645 x 565	695	x	495 x 320	1	110	635
DWS0850R	848	x	810 x 725	695	x	660 x 480	1	220	875
DWS1000R	1003	x	810 x 725	850	x	660 x 480	2	269	1030
DWS1200R	1193	x	810 x 725	1040	x	660 x 480	2	329	1150
DWS1600R	1538	x	810 x 725	1385	x	660 x 480	3	439	1405
DWS1901R	1883	x	810 x 725	1730	x	660 x 480	4	548	1680
DWS1903R	1883	x	1110 x 725	1730	x	960 x 480	4	797	2090
DWS1902	1883	x	1110 x 725	1730	x	960 x 480	4	797	2130
DWS1904	1883	x	1415 x 725	1730	x	1265 x 480	4	1050	2550

SH = Shelf

Please add 60 mm to the listed outside depth for mountings.

### [ Safes ]

### [ Type DWS ]

A distinctive feature of the DWS series safes is their solid construction plus their size (DWS 1902 and DWS1904 double-doored) and they are available with optional fire protection – tested and certified in grade LFS60P. Safes weighing less than 1.000 kg must be anchored.

### [ Product information ]

- Hinge** DIN right – model designation R (DWS1902, DWS1904 double-doored)  
option: DIN left
- Door opening angle** 180°
- Body** double-walled, reinforced, filled with armoured, high resistant barrier material
- Door structure** triple-walled, reinforced, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
- Locking mechanism** three-way moving boltwork with large steel bolts, protected by glass plate with additional emergency re-locks, fix engaging steel bolts on the hinge side
- Anchoring** fitted for floor anchoring  
anchoring bolts and shields are supplied for DWS0849, DWS0850  
option: additional anchoring holes (customer specifies position)
- Alarm connection** VdS-certified cable channels to allow connection to a burglar alarm system
- Colour** outside RAL 7035 light grey + RAL 7045 tele grey1, inside RAL 7035 light grey  
option: special colour according to RAL
- Lock** safes in grades IV and higher have to be equipped with at least 2 certified locks  
any set of locks (from VdS class 2 up) is possible
- Equipment** shelf adjustable (height setting 69 mm, DWS0849 60 mm)  
option: additional shelf, inside locker  
option (from DWS0850 up): drawer, pull-out shelf
- Accessories** option: fire protection door rebate seals, alarm switch set, interior lighting
- Option** additional certified fire protection LFS60P – except models:  
DWS0849, DWS1902, DWS1904  
bolted version – assembly on site  
from Model DWS1000 up (not possible in combination with certified fire protection)

### [ Equipment options ]

